







Boston[®]
mobile audio

Australian
Mobile Sound
Retail Price List
November 2009



SPZ Series Price List



<u>MODEL</u>	<u>DESCRIPTION</u>		<u>RRP</u> Inc GST
SPZ60 System 	2 x Type M1, 1-inch Hard Anodized Aluminium Alloy Dome Tweeters with Off-Axis AMD™ device 2 x 5¼-inch Die-Cast Aluminium Woofer baskets with 1½-inch voice coil, Glass Fibre Composite Cone, TwinStage™ heatsink and RadialVent® 2 x 24dB Bi-Ampable, System Specific, Fourth Order Crossover Networks with Aluminium Inctruded Cases Also supplied with: 2 x Flush, Angle, Surface, and 360° Full Rotation Axis Tweeter mounts 2 x 160mm, 165mm and ½ inch spacers 2 x 5x7-inch adaptor plates SYSTEM SPECIFICATIONS Frequency Response ±3dB : 50Hz – 22KHz Rec. Amplifier Power : 150 Watts – 400 Watts max. Nominal Impedance : 3 Ohm Sensitivity [1W (2.83v) at 1m] : 90db Mounting Cutout (woofer) : 127mm Mounting Depth (woofer) : 68mm		1,699.00 per pair
			1,499.00 per pair
SPZ50 System 	2 x Type M1, 1-inch Hard Anodized Aluminium Alloy Dome Tweeters with Off-Axis AMD™ device 2 x 6½-inch Die-Cast Aluminium Woofer baskets with 1½-inch voice coil, Glass Fibre Composite Cone, TwinStage™ heatsink and RadialVent® 2 x 24dB Bi-Ampable, System Specific, Fourth Order Crossover Networks with Aluminium Inctruded Cases Also supplied with: 2 x Flush, Angle, Surface, and 360° Full Rotation Axis Tweeter mounts SYSTEM SPECIFICATIONS Frequency Response ±3dB : 40Hz – 22KHz Rec. Amplifier Power : 150 Watts – 400 Watts max. Nominal Impedance : 3 Ohm Sensitivity [1W (2.83v) at 1m] : 90db Mounting Cutout (woofer) : 121mm Mounting Depth (woofer) : 62mm		1,699.00 per pair
			1,499.00 per pair

WARRANTY: 1 year parts & labour warranty covers manufacturing defects only

EXTENDED WARRANTY: 1 additional year warranty if installed by an Authorised Boston dealer

PRICES SUBJECT TO CHANGE WITHOUT NOTICE, R.R.P. IS A RECOMMENDATION ONLY AND INCLUDES GST

ProSE Series Price List

MODEL	DESCRIPTION			RRP Inc GST
Pro60SE System	2 x Type M1, 1-inch Hard Anodized Aluminium Alloy Dome Tweeters with Full AMD™ device			999.00 per pair
	2 x 6½-inch Cast Aluminium Woofer baskets with 1½-inch voice coil, Copolymer Cone, NeoDymium magnet, TwinStage™ heatsink and RadialVent®			
	2 x Bi-Ampable, System Specific, Crossover Networks with Aluminium Intruded Cases			
	Also supplied with:			
	2 x Flush, Angle, Surface, Tweeter mounts			
	2 x Adapter rings			
	SYSTEM SPECIFICATIONS			
	Frequency Response ±3dB : 50Hz – 22KHz			
	Rec. Amplifier Power : 125 Watts			
	Nominal Impedance : 3 Ohm			
	Sensitivity [1W (2.83v) at 1m] : 90db			
	Mounting Cutout (woofer) : 127mm			
	Mounting Depth (woofer) : 60mm (52mm with supplied spacer)			
				899.00 per pair
Pro50SE System	2 x Type M1, 1-inch Hard Anodized Aluminium Alloy Dome Tweeters with Full AMD™ device			999.00 per pair
	2 x 5¼-inch Cast Aluminium Woofer baskets with 1½-inch voice coil, Copolymer Cone, NeoDymium magnet, TwinStage™ heatsink and RadialVent®			
	2 x Bi-Ampable, System Specific, Crossover Networks with Aluminium Intruded Cases			
	Also supplied with:			
	2 x Flush, Angle, Surface, Tweeter mounts			
	2 x Adapter rings and spacers			
	SYSTEM SPECIFICATIONS			
	Frequency Response ±3dB : 60Hz – 22KHz			
	Rec. Amplifier Power : 125 Watts			
	Nominal Impedance : 3 Ohm			
	Sensitivity [1W (2.83v) at 1m] : 90db			
	Mounting Cutout (woofer) : 121mm			
	Mounting Depth (woofer) : 59mm			
				899.00 per pair
Pro Imaging System				
Neo TMSE	Type M2, 1-inch Anodised alloy dome Tweeters with Slim AMD™ device. Axis, flush, surface, and angle tweeter mounting kit, plus separable Dockable crossovers. Used with Pro50/Pro60 or stand alone.			399.00 per pair



WARRANTY: 1 year parts & labour warranty covers manufacturing defects only

EXTENDED WARRANTY: 1 additional year warranty if installed by an Authorised Boston dealer

PRICES SUBJECT TO CHANGE WITHOUT NOTICE, R.R.P. IS A RECOMMENDATION ONLY AND INCLUDES GST

SR Series Price List



<u>MODEL</u>	<u>DESCRIPTION</u>			<u>RRP</u> Inc GST
<u>SR Series Component Systems</u>				
SR60 	6½-inch copolymer cone woofer with butyl rubber surround, 1½-inch voice coil, neodymium magnet structure and TwinStage™ heatsink. Type S1, 1-inch Kortec® dome tweeter. Separable and Dockable, multi-element, application specific crossovers. Cutout (woofer): 133mm, Mounting Depth (woofer): 62mm			499.00 pr
SR50 	5¼-inch copolymer cone woofer with butyl rubber surround, 1½-inch voice coil, neodymium magnet structure and TwinStage™ heatsink. Type S1, 1-inch Kortec® dome tweeter. Separable and Dockable, multi-element, application specific crossovers. Cutout (woofer): 116mm, Mounting Depth (woofer): 57mm			499.00 pr
<u>SR Series Coaxial Systems</u>				
SR65 	6½-inch coaxial speaker with copolymer cone woofer with butyl rubber surround, 1½-inch voice coil, neodymium magnet structure and TwinStage™ heatsink. Type S1, 1-inch Kortec® dome tweeter. CATB™ baffle greatly improves on and off axis tweeter response. Integrated multi-element crossovers. Cutout: 133mm, Mounting Depth: 62mm			349.00 pr
SR55 	5¼-inch coaxial speaker with copolymer cone woofer with butyl rubber surround, 1½-inch voice coil, neodymium magnet structure and TwinStage™ heatsink. Type S1, 1-inch Kortec® dome tweeter. CATB™ baffle greatly improves on and off axis tweeter response. Integrated multi-element crossovers. Cutout: 116mm, Mounting Depth: 57mm			349.00 pr
SR80 	5 x 7-inch plate speaker, with a 6½-inch copolymer woofer with butyl rubber surround, 1½-inch voice coil, neodymium magnet structure and TwinStage™ heatsink. Type S1, 1-inch Kortec® tweeter. Integrated multi-element crossovers. – <i>No Grilles</i> Cutout: Standard 5 x 7 inch, Mounting Depth: 61mm			399.00 pr
SR95 	6 x 9-inch copolymer cone woofer with butyl rubber surround, 1½-inch voice coil, neodymium magnet structure and TwinStage™ heatsink. Dual Type S1, 1-inch Kortec® dome tweeters for smoother frequency response and higher output. CATB™ baffle greatly improves on and off axis tweeter response. Integrated multi-element crossovers. Cutout: Standard 6 x 9 inch, Mounting Depth: 67mm			399.00 pr
<u>SR Imaging System</u>				
ISTS	Type S1, 1-inch Kortec® dome tweeters with axis, flush, surface, and angle tweeter mounting kit and separable dockable crossovers included. Used with SR60, SL60 or stand alone.			299.00 pr









WARRANTY: 1 year parts & labour warranty covers manufacturing defects only

EXTENDED WARRANTY: 1 additional year warranty if installed by an Authorised Boston dealer

PRICES SUBJECT TO CHANGE WITHOUT NOTICE, R.R.P. IS A RECOMMENDATION ONLY AND INCLUDES GST

SC Series Price List













<u>MODEL</u>	<u>DESCRIPTION</u>		<u>RRP</u> <u>Inc GST</u>
<u>SC Series Components</u>			
SC60 	High performance, low profile component system, featuring a 6½-inch copolymer cone woofers with butyl rubber surrounds, type S2, ¾-inch soft dome tweeter with AMD™ device for improved high frequency response. Flush/Angle and Surface tweeter mounting kit included. System-specific, separable or dockable crossovers. Cutout (woofer): 131mm, Mounting Depth (woofer): 61mm		399.00 pr
SC50 	High Performance, low profile component system, featuring a 5¼-inch copolymer cone woofers with butyl rubber surrounds, type S2, ¾-inch soft dome tweeter with AMD™ device for improved high frequency response. Flush/Angle and Surface tweeter mounting kit included. System-specific, separable or dockable crossovers. Cutout (woofer): 116mm, Mounting Depth (woofer): 55mm		399.00 pr
<u>SC Series Coaxials</u>			
SC65 	6-inch copolymer cone woofers with butyl rubber surround and 1½-inch voice coil. Type S2, ¾-inch Kortec dome tweeters. Neodymium magnets for both woofer and tweeter. Supplied with various mounting rings. Cutout: 131mm, Mounting Depth: 61mm		249.00 pr
SC55 	5¼-inch copolymer cone woofers with butyl rubber surround and 1½-inch voice coil. Type S2, ¾-inch Kortec dome tweeters. Neodymium magnets for both woofer and tweeter. Cutout: 116mm, Mounting Depth: 55mm		249.00 pr
SC85 	5 x 7-inch copolymer cone woofers with butyl rubber surround. and 1½-inch voice coil. Type S2, ¾-inch Kortec dome tweeters. Neodymium magnets for both woofer and tweeter. – <i>No Grilles</i> Cutout: Standard 5 x 7 inch, Mounting Depth: 56mm		299.00 pr
SC95 	6 x 9-inch copolymer cone woofers with butyl rubber surround and 1½-inch voice coil, and Dual type S2, ¾-inch Kortec dome tweeters. Neodymium magnets for both woofer and tweeter. Cutout: Standard 6 x 9 inch, Mounting Depth: 66mm		299.00 pr



WARRANTY: 1 year parts & labour warranty covers manufacturing defects only
EXTENDED WARRANTY: 1 additional year warranty if installed by an Authorised Boston dealer
 PRICES SUBJECT TO CHANGE WITHOUT NOTICE, R.R.P. IS A RECOMMENDATION ONLY AND INCLUDES GST

S Series Price List










<u>MODEL</u>	<u>DESCRIPTION</u>			<u>RRP</u> Inc GST
<u>S Series Components</u>				
S60 	6½-inch copolymer cone woofers with butyl rubber surrounds. Type S3, ¾-inch soft dome tweeter with AMD™ device for improved high frequency response. Flush/Angle- and Surface tweeter mounting kit. System-specific crossovers. Cutout (woofer): 142mm, Mounting Depth (woofer): 63mm			249.00 pr
S50 	5¼-inch copolymer cone woofers with butyl rubber surrounds. Type S3, ¾-inch soft dome tweeter with AMD™ device for improved high frequency response. Flush/Angle- and Surface tweeter mounting kit. System-specific crossovers. Cutout (woofer): 117mm, Mounting Depth (woofer): 47mm			249.00 pr
<u>S Series Coaxials</u>				
S35 	3½-inch copolymer cone woofers with butyl rubber surrounds. Type S3, ¾-inch soft dome tweeter with AMD™ device for improved high frequency response. Easy "drop-in" installation – <i>No Grilles</i> Cutout: 81mm, Mounting Depth: 42mm			79.00 pr
S45 	4-inch copolymer cone woofers with butyl rubber surrounds. Type S3, ¾-inch soft dome tweeter with AMD™ device for improved high frequency response. Easy "drop-in" installation – <i>No Grilles</i> Cutout: 96mm, Mounting Depth: 52mm			79.00 pr
S55 	5¼-inch copolymer cone woofers with butyl rubber surrounds. Type S3, ¾-inch soft dome tweeter with AMD™ device for improved high frequency response. Easy "drop-in" installation. Cutout: 117mm, Mounting Depth: 47mm			109.00 pr
S65 	6½-inch copolymer cone woofers with butyl rubber surrounds. Type S3, ¾-inch soft dome tweeter with AMD™ device for improved high frequency response. Easy "drop-in" installation. Cutout: 142mm, Mounting Depth: 63mm			139.00 pr
S65RC 	Designed to fit Honda and shallow mount locations. 6-inch copolymer cone woofers with butyl rubber surrounds. Type S3, ¾-inch soft dome tweeter with AMD™ device for improved high frequency response. Easy "drop-in" installation.– <i>No Grilles</i> Cutout: 128mm, Mounting Depth: 50mm			139.00 pr
S75 	4 x 6-inch copolymer cone woofers with butyl rubber surrounds and Type S3, ¾-inch soft dome tweeter with AMD™ device for improved high frequency response. Easy "drop-in" installation. – <i>No Grilles</i> Cutout: Standard 4 x 6 inch, Mounting Depth: 46mm			89.00 pr
S85 	5 x 7-inch copolymer cone woofers with butyl rubber surrounds and Type S3, ¾-inch soft dome tweeter with AMD™ device for improved high frequency response. Easy "drop-in" installation – <i>No Grilles</i> Cutout: Standard 5 x 7 inch, Mounting Depth: 57mm			139.00 pr
S953 	6 x 9-inch copolymer cone woofers with butyl rubber surround. 2½-inch midrange driver and a Type S3, ¾-inch soft dome tweeter with AMD™ device for improved high frequency response. Easy "drop-in" installation. Cutout: Standard 6 x 9 inch, Mounting Depth: 81mm			199.00 pr

WARRANTY: 1 year parts & labour warranty covers manufacturing defects only

EXTENDED WARRANTY: 1 additional year warranty if installed by an Authorised Boston dealer

PRICES SUBJECT TO CHANGE WITHOUT NOTICE, R.R.P. IS A RECOMMENDATION ONLY AND INCLUDES GST

Subwoofer Price List





<u>MODEL</u>	<u>DESCRIPTION</u>		<u>RRP</u> Inc GST
G108-4 (single 4Ω) G108-44 (dual 4Ω) 	4 ohm, single or dual voice coil, 8-inch subwoofer. Patented RadialVent cooling, 2-inch, 4 layer voice coil, and SureSet™ overdrive protection. Dual Voice Coil model also has impedance selection. Optimised for a 0.3 cu.ft box. – <i>No Grille</i> Mounting Depth: 107mm		179.00 ea
G110-4 (single 4Ω) G110-44 (dual 4Ω) 	4 ohm, single or dual voice coil, 10-inch subwoofer. Patented RadialVent cooling, 2-inch, 4 layer voice coil, and SureSet™ overdrive protection. Dual Voice Coil model also has impedance selection. Optimised for a 0.5 cu.ft box. – <i>No Grille</i> Mounting Depth: 120mm		229.00 ea  199.00 ea
G112-4 (single 4Ω) G112-44 (dual 4Ω)	4 ohm, single or dual voice coil, 12-inch subwoofer. Patented RadialVent cooling, 2-inch, 4 layer voice coil, and SureSet™ overdrive protection. Dual Voice Coil model also has impedance selection. Optimised for a 1 cu.ft box. – <i>No Grille</i> Mounting Depth: 126mm		269.00 ea  229.00 ea
G210-4 (single 4Ω) G210-44 (dual 4Ω) 	4 ohm, single or dual voice coil, 10-inch subwoofer. Patented RadialVent cooling, 2½-inch voice coil, and SureSet™ overdrive protection. Dual Voice Coil model also has impedance selection. Optimised for a 0.5 cu.ft box. – <i>No Grille</i> Mounting Depth: 172mm		349.00 ea  269.00 ea
G212-4 (single 4Ω) G212-44 (dual 4Ω)	4 ohm, single or dual voice coil, 12-inch subwoofer. Patented RadialVent cooling, 2½-inch voice coil, and SureSet™ overdrive protection. Dual Voice Coil model also has impedance selection. Optimised for a 1 cu.ft box. – <i>No Grille</i> Mounting Depth: 187mm		309.00 ea  299.00 ea
G310-4 (single 4Ω) G310-44 (dual 4Ω) 	4 ohm, single or dual voice coil, 10-inch subwoofer. Rigid cast aluminium chassis with patented RadialVent cooling and 2¾-inch voice coil. Dual Voice Coil model also has impedance selection. Optimised to fit into a 0.5 cu.ft box. – <i>No Grille</i> Mounting Depth: 162mm	247.50 ea	369.00 ea
G312-4 (single 4Ω) G312-44 (dual 4Ω) 	4 ohm, single or dual voice coil, 12-inch subwoofer. Rigid cast aluminium chassis with patented RadialVent cooling and 2¾-inch voice coil. Dual Voice Coil model also has impedance selection. Optimised to fit into a 1 cu.ft box. – <i>No Grille</i> Mounting Depth: 178mm	264.00 ea	399.00 ea

WARRANTY: 1 year parts & labour warranty covers manufacturing defects only

EXTENDED WARRANTY: 1 additional year warranty if installed by an Authorised Boston dealer

PRICES SUBJECT TO CHANGE WITHOUT NOTICE, R.R.P. IS A RECOMMENDATION ONLY AND INCLUDES GST

Subwoofer Price List

<u>MODEL</u>	<u>DESCRIPTION</u>	<u>Stockist Inc GST</u>	<u>RRP Inc GST</u>
G510-4 (single 4Ω) G510-44 (dual 4Ω) 	4 ohm, single or dual voice coil, 10-inch subwoofer. Rigid cast aluminium chassis with patented RadialVent cooling and 2¾-inch voice coil. Dual Voice Coil model also has impedance selection. Optimised to fit into a 0.5 cu.ft box. – <i>No Grille</i> Mounting Depth: 162mm		509.00 ea  469.00 ea
G512-4 (single 4Ω) G512-44 (dual 4Ω)	4 ohm, single or dual voice coil, 12-inch subwoofer. Rigid cast aluminium chassis with patented RadialVent cooling and 2¾-inch voice coil. Dual Voice Coil model also has impedance selection. Optimised to fit into a 1 cu.ft box. – <i>No Grille</i> Mounting Depth: 178mm		609.00 ea  499.00 ea
SPG555-2 (single 2Ω) SPG555-4 (single 4Ω) 	REFERENCE Subwoofer. Surface area of 555 cm ² , 3½-inch voice coil, 4 ohm, patented RadialVent cooling, and Neodymium magnet structure. This monster can be stripped and painted or plated in the field. The Voice coil can also be replaced in the field. THIS SUB HAS NO COMPETITORS. Optimised to fit into a 1 cu.ft box. – <i>No Grille</i> Mounting Depth: 210mm		999.00 ea
<u>Tunable Radiators</u>			
SPG-TR	SPG-TR Tunable Radiators™ increase overall bass output without adding enclosure volume. Unique user tunable adjustments allow for optimum performance. – <i>No Grille</i> Mounting Depth: 41mm		299.00 ea
GTR-12	12-inch GTR Tunable Radiators™ increase overall bass output without adding enclosure volume. Unique user tunable adjustments allow for optimum performance. – <i>No Grille</i> Mounting Depth: 41mm		249.00 ea
GTR-10	10-inch GTR Tunable Radiators™ increase overall bass output without adding enclosure volume. Unique user tunable adjustments allow for optimum performance. – <i>No Grille</i> Mounting Depth: 41mm		199.00 ea
<u>Subwoofer Replacement Parts</u>			
SPG-RVC	Replacement Voice Coil for SPG555 Subwoofer. <i>Available as 2 or 4 Ohm.</i>		199.00 ea
SPG-SPS	Soft Part System Replacement for SPG555		199.00 ea
G512-4-SPS G512-44-SPS	Soft Part System Replacement for G5 Series, 12 inch Subwoofer <i>Includes Voice Coil (4 Ohm or Dual 4 Ohm)</i>		299.00 ea
G510-4-SPS G510-44-SPS	Soft Part System Replacement for G5 Series, 10 inch Subwoofer <i>Includes Voice Coil (4 Ohm or Dual 4 Ohm)</i>		249.00 ea








WARRANTY: 1 year parts & labour warranty covers manufacturing defects only

EXTENDED WARRANTY: 1 additional year warranty if installed by an Authorised Boston dealer

PRICES SUBJECT TO CHANGE WITHOUT NOTICE, R.R.P. IS A RECOMMENDATION ONLY AND INCLUDES GST

GT Amplifier Price List





<u>MODEL</u>	<u>DESCRIPTION</u>	<u>Stockist Inc GST</u>	<u>RRP Inc GST</u>
GT275 	2 Channel High-Current/High-Power design Amplifier with built-in Crossover/EQ. 2 ohms Mono stable. 2 x 75w (4 ohm) or 2 x 120w (2 ohm) 1 x 225w (4 ohm) or 1 x 300w (2 ohm) Dimensions (Height + Width + Depth): 61 x 223 x 229mm		499.00
GT2125 	2 Channel Amplifier. High-Current/High-Power design with built-in Crossover/EQ. 2 ohms Mono stable. 2 x 125w (4 ohm) or 2 x 200w (2 ohm) 1 x 400w (4 ohm) or 1 x 600w (2 ohm) Dimensions (Height + Width + Depth): 61 x 337 x 229mm		699.00
GT2200 	2 Channel Amplifier. High-Current/High-Power design with built-in Crossover/EQ. 2 ohms Mono stable. 2 x 200w (4 ohm) or 2 x 350w into (2 ohm) 1 x 700w (4 ohm) or 1 x 900w (2 ohm) Dimensions (Height + Width + Depth): 61 x 477 x 229mm		899.00
GT2300 	2 Channel Amplifier. High-Current/High-Power design with built-in Crossover/EQ. 2 ohms Mono stable. 2 x 300w (4 ohm) or 2 x 500w (2 ohm) 1 x 1,000w (4 ohm) or 1 x 1,400w (2 ohm) Dimensions (Height + Width + Depth): 61 x 566 x 229mm		1,299.00
GT475 	4/3/2 Channel Amplifier. High-Current/High-Power design with built-in Crossover/EQ. 2 ohms Mono stable. 4 x 75w (4 ohm) or 4 x 120w (2 ohm) 2 x 225w (4 ohm) or 2 x 250w (2 ohm) 2 x 75w + 1 x 225w (4 ohm) or 2 x 120w + 1 x 250w (2 ohm) Dimensions (Height + Width + Depth): 61 x 375 x 229mm		799.00
GT4100 	4/3/2 Channel Amplifier. High-Current/High-Power design with built-in Crossover/EQ. 2 ohms Mono stable. 4 x 100w (4 ohm) or 4 x 150w (2 ohm) 2 x 300w (4 ohm) / 2 x 450w (2 ohm) or 2 x 100w + 1 x 300w (4 ohm) or 2 x 100w + 1 x 450w (2 ohm) Dimensions (Height + Width + Depth): 61 x 566 x 229mm		1,199.00
GT5750 	5 Channel Amplifier. High-Current/High-Power design with built-in Crossover/EQ. 2 ohms Mono stable. 4 x 75w (4 ohm) + 1 x 200w (4 ohm) 4 x 100w (4 ohm) + 1 x 375w (2 ohm) Dimensions (Height + Width + Depth): 61 x 566 x 229mm		1,299.00
GT-RSL	Optional Remote Subwoofer Level Control, compatible with GT2200, GT2300, GT475, GT4100, GT5750, GT24, GT28, GT40, GT42, GT50		119.00



WARRANTY: 1 year parts & labour warranty covers manufacturing defects only
EXTENDED WARRANTY: 1 additional year warranty if installed by an Authorised Boston dealer
 PRICES SUBJECT TO CHANGE WITHOUT NOTICE, R.R.P. IS A RECOMMENDATION ONLY AND INCLUDES GST

GTA Amplifier Price List



<u>MODEL</u>	<u>DESCRIPTION</u>		<u>RRP</u> Inc GST
GTA502 	2 channel High efficiency Class AB design. Boston's Q-Tune™ circuitry for Simple Bass Output Optimization. SST™ (Symmetrical Signal Topology) system uses balanced asymmetrical inputs for noise cancellation. Fully adjustable and selectable Lowpass/Highpass crossovers. 2 x 50w (4 ohms) or 2 x 80w (2 ohms) 1 x 160w (4 ohms) Dimensions (Height + Width + Depth): 61 x 238 x 211mm		299.00
GTA504 	4 Channel High efficiency Class AB design. Boston's Q-Tune™ circuitry for Simple Bass Output Optimization. SST™ (Symmetrical Signal Topology) system uses balanced asymmetrical inputs for noise cancellation. Fully adjustable and selectable Lowpass/Highpass crossovers. 4 x 50w (4 ohms) or 4 x 80w (2 ohms) 2 x 160w (4 ohms) Dimensions (Height + Width + Depth): 61 x 375 x 211mm		399.00
GTA802 	2 channel High efficiency Class AB design. Boston's Q-Tune™ circuitry for Simple Bass Output Optimization. SST™ (Symmetrical Signal Topology) system uses balanced asymmetrical inputs for noise cancellation. Fully adjustable and selectable Lowpass/Highpass crossovers. 2 x 80w (4 ohms) or 2 x 130w (2 ohms) 1 x 250w (4 ohms) Dimensions (Height + Width + Depth): 61 x 298 x 211mm		399.00
GTA400M 	Monoblock High efficiency Class AB design. Boston's Q-Tune™ circuitry for Simple Bass Output Optimization. SST™ (Symmetrical Signal Topology) system uses balanced asymmetrical inputs for noise cancellation. Fully adjustable and selectable Lowpass/Highpass crossovers. 1 x 250w (4 ohms) or 1 x 400w (2 ohms) Dimensions (Height + Width + Depth): 61 x 268 x 211mm		499.00
GT800M 	Monoblock High efficiency Class AB design. Boston's Q-Tune™ circuitry for Simple Bass Output Optimization. SST™ (Symmetrical Signal Topology) system uses balanced asymmetrical inputs for noise cancellation. Fully adjustable and selectable Lowpass/Highpass crossovers. 1 x 500w (4 ohms) or 1 x 800w (2 ohms) Dimensions (Height + Width + Depth): 61 x 318 x 211mm		699.00
GTA1005 	5 Channel High efficiency Class AB design. Boston's Q-Tune™ circuitry for Simple Bass Output Optimization. SST™ (Symmetrical Signal Topology) system uses balanced asymmetrical inputs for noise cancellation. Fully adjustable and selectable Lowpass/Highpass crossovers. 4 x 50w + 1 x 250w (4 ohms) 4 x 80w + 1 x 400w (2 ohms) or 2 x 160w + 1 x 250w (4 ohm) Dimensions (Height + Width + Depth): 61 x 538 x 229mm		699.00
GTA-RSL	Optional Remote Subwoofer Level Control, compatible with GTA502, GTA504, GTA802, GTA400M, GTA800M AND GTA1005		49.00

WARRANTY: 1 year parts & labour warranty covers manufacturing defects only

EXTENDED WARRANTY: 1 additional year warranty if installed by an Authorised Boston dealer

PRICES SUBJECT TO CHANGE WITHOUT NOTICE, R.R.P. IS A RECOMMENDATION ONLY AND INCLUDES GST