

COMPONENT SYSTEMS

RRP (inc. GST)

LOTUS REFERENCE COMPONENT SET

\$1,700.00



- 2 x RT27F Tweeters
- 2 x RW165/1 Woofers
- 2 x RX2.5H High-pass Crossovers
- 2 x RX2.5L Low-pass Crossovers



- Accessories include tweeter cables, mounting clamps, woofer grilles, screws, emblems, stickers, manual & protective gloves.

LOTUS PERFORMANCE COMPONENT SET

\$1300.00



- 2 x PT27F Tweeters
- 2 x PW165/1 Woofers
- 2 x PX3.0 Crossovers

- Accessories include tweeter cables, mounting clamps, woofer grilles, screws, emblems, stickers & manual.

SUBWOOFERS

SW-250/1 (10")

\$890.00



- Precision Aluminium cone: 250mm (10")
- Nominal impedance: 4ohm
- Sensitivity: 91.5dB
- Free air resonance: 31Hz
- Nominal/max power handling: 150/400w
- Enclosure size: (sealed) 20 litres, (Vented) 37 litres
- Mounting depth: 128mm
- Weight: 7.0Kg (total), 2.7Kg (magnet)
- Linear coil travel (P-P): 22mm



SW-300/1 (12")

\$990.00



- Precision Aluminium cone: 300mm (12")
- Nominal impedance: 4ohm
- Sensitivity: 92 dB
- Free air resonance: 23Hz
- Nominal/max power handling: 180/500w
- Enclosure size: (sealed) 38 litres, (Vented) 64 litres
- Mounting depth: 146mm
- Weight: 7.4Kg (total), 2.7Kg (magnet)
- Linear coil travel (P-P): 27mm

SEPERATE COMPONENTS - TWEETERS
RRP (inc. GST)
RT27F - REFERENCE TWEETER
**\$290.00
(each)**


27mm Pre-coated fabric dome material
Nominal impedance: 6 ohm
Sensitivity: 90 dB
Free air resonance: 800 Hz
Nominal/max power handling: 80/180* w

PT27F - PERFORMANCE TWEETER
**\$150.00
(each)**


27mm Pre-coated fabric dome material
Nominal impedance: 6 ohm
Sensitivity: 89.5 dB
Free air resonance: 1000 Hz
Nominal/max power handling: 80/180* w

SEPERATE COMPONENTS - MIDRANGE
RM120 - REFERENCE MIDRANGE
**\$290.00
(each)**


120mm special coated paper cone
Nominal impedance: 4 ohm
Sensitivity: 90.5 dB
Free air resonance: 71 Hz
Nominal/max power handling: 110/400* w

SEPERATE COMPONENTS - WOOFERS
RW165/1 - REFERENCE 6.5" WOOFER
**\$400.00
(each)**


165mm precision lightweight magnesium cone
Nominal impedance: 4 ohm
Sensitivity: 88.5 dB
Free air resonance: 64 Hz
Nominal/max power handling: 100/250 w

PW165/1 - PERFORMANCE 6.5" WOOFER
**\$250.00
(each)**


165mm lightweight fibreglass cone
Nominal impedance: 4 ohm
Sensitivity: 90 dB
Free air resonance: 64 Hz
Nominal/max power handling: 100/250 w

RW220 - REFERENCE 8" WOOFER
**\$440.00
(each)**


220mm injection moulded magnesium cone
Nominal impedance: 4 ohm
Sensitivity: 91 dB
Free air resonance: 29 Hz
Nominal/max power handling: 110/300 w

* Maximum power with recommended SEAS crossover

Reference audio
Distributors of the worlds finest hifi products

visual P/L

Reference Audio Visual Pty Ltd - ABN 14 105 491 361 - P.O. Box 171, Park Orchards VIC 3114

FreeCall: 1800 133 135

Fax: (03) 8813 0133

Email: michael@referenceav.com.au

www.referenceav.com.au